

DOWNLIGHTS

LED-Gallery 3

ADO Lights by TTC Timmler Technology GmbH
 Christian-Schäfer-Str. 8 | 53881 Flammersheim
 T +49 2255 9212-00 | F +49 2255 9212-99
 info@ado-lights.com | www.ado-lights.com



BASE INFO, PICTURES AND TECHNICAL DRAWINGS



DIMENSIONS [L X W X H]	Luminaire housing: 98 x 48 x 49 mm Cut-out: 90 x 40 mm
POWER CONSUMPTION	7 W 3 reflectors
LUMINOUS FLUX	450 lm 500 lm 600 lm
LIGHT BEAM ANGLE	15°/30°/45° rigid
SERVICE LIFE	LED 50,000 hours at 70% of mean luminous flux
COLOUR TEMPERATURE	White 2,700/3,000/4,000 Kelvin
CRI	CRI > 90
CONTROL INTERFACE	With ballast, not dimmable
IP RATING	IP20

LUMINAIRE HOUSING	Aluminium powder-coated white, black or grey
CONVERTER	Overload protection Overtemperature protection Short-circuit protection
OPTIONAL	Dimmable ballast 1–10 V DALI Connection cable With 6 mm polished glass covering IP54 PoE-enabled
LIGHT CALCULATION	EULUM data see www.ado-lights.com

